


Entry/Exit Station


Section Control Station



LS Station



Entry/Exit Station



Section Control Station

BASE MODEL

Multilingual high contrast LCD display for user instructions (4x20 characters)

Read/Write ticket unit for Magnetic stripe or Barcode tickets

Illuminated navigation to guide customers step-by-step

Stainless steel cabinet

Standard color - Housing (RAL 9006 White Aluminium) plus side/front panels (RAL 7021 Black Grey)

Peripheral control unit

Power Supply

Heating and cooling units with separate thermostats

Intercom call button and loudspeaker

Individual security lock

OPTIONS

10.4" color TFT display and touchscreen

Range of contactless RFID proximity readers

Range of long range AVI readers

Customized side/front panel color

Customized housing and side/front panel colors

Sea/Ocean special protective treatment

Valiscan barcode scanner (1D or 2D options)

Variety of base heights (standard 60mm, increased height 200mm)

Door open sensor options

Proximity and AVI operation only (Section Control Station only)

Double height frame (truck and car) for LE/ LX/ LS

ZEAG Section Control Station gives a high level of flexibility to allow control of vehicles in and out of controlled sectors within a parking facility (e.g. nested areas)

STANDARD FEATURES

- Read/Write ticket unit for magnetic stripe or barcode tickets
- Online operation (RS422/485 or TCP/IP) or standalone
- Contract, Season or Monthly parking using a wide range of media (magnetic cards, barcode, proximity, AVI, LPR)
- PCI-DSS certified together with Parking Management System
- Barrier gate control



LS Station

Dimensions

- Width: 460mm / 18,1"
- Height: 1360mm / 53,3" (including standard base)
- Height: 1500mm / 59,1" (including Chip & PIN base)
- Depth: 422mm / 16,6"
- Standard height base: 60mm / 2,4"
- Increased height base for Chip & PIN: 200mm / 7,9"
- Weight: 53 kg / 117 lbs approx. (incl. standard base)

Power

- 90 to 240 VAC, 47 to 63 Hz

Power Consumption

- Regular load: 114 W
- With heating: 350 W

Environment

- Ambient temperature: -20°C / -4 F to +50°C / 122 F