

## Basic Wallbox Series - CCL-WB MIX

| Type                              | CCL-WB MIX   |                  |
|-----------------------------------|--|------------------|
| Code                              | 490076   |                  |
| Number of sockets                 | 2  |                  |
| Input                             |  |                  |
| AC power supply                   | 1P + N + PE  | 3P + N + PE      |
| AC Voltage                        | 230 AC +/- 10% *                                   | 400 V AC +/- 10% |
| Nominal input current             | 48 A   |                  |
| Nominal input power               | 3,6 kW   | 22 kW            |
| Required power supply capacity    | 3,6 kVA  | 22 kVA           |
| Frequency                         | 50 / 60 Hz   |                  |
| Output                            |  |                  |
| Maximum output power              | 7,3 kW (Socket A)                                  | 21 kW (Socket B) |
| Maximum output current            | 16 A (Socket A)                                    | 32 A (Socket B)  |
| AC output voltage                 | 230V AC +/- 10%                                    | 400V AC +/- 10%  |
| Charge system                     |  |                  |
| Socket A                          | Mode 3 (IEC 61851)<br>Type 2 (UNE EN 62196-2)      |                  |
| Socket B                          | Mode 1 & Mode 2<br>CEE 7/4 (Schuko) or BS1363 (UK) |                  |
| General                           |  |                  |
| Cable length                      | -  |                  |
| Enclosure rating                  | IP 54 / IK 10                                      |                  |
| Enclosure material                | ABS plastic  |                  |
| Installation mode                 | Simple installation, 4-point wallfixing            |                  |
| Power limit control               | Mode 3 PWM control according ISO/IEC 61851-1       |                  |
| Operating temperature             | -10 to +45 °C                                      |                  |
| Operating humidity                | To 95% RH Non-condensing                           |                  |
| Net weight                        | 4 Kg   |                  |
| Optional devices                  |  |                  |
| Extended Temperature range        | Heater (-30 to + 45 °C)                            |                  |
| * depending on local installation |  |                  |

