

Basic Wallbox Series - CCL-WBM

Type		CCL-WBM
Code		490072
Number of sockets		1
Input		
AC power supply *		1P + N + PE 3P + N + PE
AC Voltage		230AC +/- 10% 400 V AC +/- 10%
Nominal input current **		32 A 32 A
Nominal input power		7,2 k 21 kW
Required power supply capacity		7,2 kVA 21 kVA
Frequency		50 / 60 Hz 50 / 60 Hz
Output		
Maximum output power		7,2 kW 21 kW
Maximum output current		32 A 32 A
AC output voltage		230 V AC +/- 10% 400 V AC +/- 10%
Charge system		
Socket A		Mode 3 (IEC 61851) Type 2 (UNE EN 62196-1)
Socket B		-
General		
Cable lenght		-
Enclosure rating		IP 54 / IK 10
Enclosure material		ABS plastic
Installation mode		Simple installation, 4-point wallfixing
Power limit control		Mode 3 PWM control according ISO/IEC 61851-1
Operating temperature		-10 to +45 °C
Operating humidity		To 95% RH Non-condensing
Light beacon		Three color led status
Net weight		4 Kg
Optional devices		
Extended Temperature range		Heater (-30 to + 45 °C)
Tethered cable		Type 2 (5 meters length)
* depending on local installation		
**power limit control by software		

