

Charging Post- CCL-PT3 63

Type	CCL-PT3 63
Code	490126
Number of sockets	1
Input	
AC power supply	3P + N + PE
AC Voltage	400V AC +/- 10%
Nominal input current*	63 A
Nominal input power	43 kW
Required power supply capacity	43,6 kVA
Frequency	50 / 60 Hz
Output	
Maximum output power	43 kW (Socket A)
Maximum output current*	63 A (Socket A)
AC output voltage	400 V AC 3P + N
Charge system	
Socket A	Mode 3 (IEC 61851) Type 2 tethered cable (UNE EN 62196-2)
Electrical protections	
Overcurrent protections	MCB autorecovery
Safety protection	RCD 30mA autorecovery (class A)
Energy meter	
Accuracy class in active energy	Class 1 - EN50470-3
Accuracy class in reactive energy	Class 2 - EN62053-23
Meter standards	EN62052-11, EN62053-21, EN62053-23, EN61010-1
Network connection	
Ethernet	10/100BaseTX (TCP-IP)
General	
Enclosure rating	IP 54 / IK 10
Enclosure material	Polyurethane casing
Socket protection	Vandal metal doors
Operating temperature	-30 to + 45 °C (Heater system included)
Operating humidity	To 95% RH Non-condensing
RFID system	ISO / IEC 14443A / B
Display	LCD Backlight double line text
Rear Light beacon	Three color led status
Power limit control	Mode 3 PWM control according ISO/IEC 61851-1
Interface protocol	OCCP / XML
Net weight	65 Kg
Optional devices	
Wireless Communication	3G / GPRS
RCD Protection	RCD class B
Overvoltage protection	"Transient surge protector Type 2 (EN 61643-11)"
* Adjustable power limit control	

