

### Description

The JSL-I7A is a stylish 7-inch Linux-based indoor monitor designed for advanced video intercom systems. It supports video calls, remote unlocking, real-time monitoring of outdoor stations, and intercom between apartments. With its HD capacitive touch screen, intuitive interface, and versatile connectivity options, the H70 provides enhanced home security and convenience for residential and commercial applications.



### Main Features

- 7-inch Capacitive Touch Screen — Clear IP color image with 1024×600 resolution for vivid visuals.
- Elegant & Stylish Design — Available in White & Black color with durable plastic panel.
- Multi-point Communication — Supports calls between residents, guard stations, and multiple indoor monitors in the same apartment.
- Remote Door Control — Unlock doors directly from the monitor during intercom or monitoring.
- Flexible Monitoring — Real-time video monitoring of outdoor stations and additional IP cameras.
- Inter-apartment Intercom — Supports communication between different apartments.
- Built-in Application Connectivity — For enhanced smart home integration.
- Multiple Installation Options — Flush or surface mounting available.
- Customizable User Experience — Adjustable bell and voice volume, mute function, multiple ringtones.
- Security Functions — Leave messages with photos, record visitors, and view logs by date.
- Power over Ethernet (PoE) — Supports both 24V non-standard and 48V standard PoE.
- Extra Control Features — Option to call elevator, order/send elevator, call guard station.
- Multilingual Menu — English and other language options available.

### Specification

<b>System</b>	Linux
<b>Panel Material</b>	Plastic
<b>Color</b>	White & Black
<b>Display</b>	7-inch capacitive touch screen
<b>Resolution</b>	480×272 (Panel) / Sharp IP Color Image 1024×600
<b>Operation</b>	Capacitive pushbutton + touch screen
<b>Speaker</b>	8Ω, 1.5W/2W
<b>Microphone</b>	-56dB
<b>Alarm Input</b>	4 alarm inputs
<b>Power Supply</b>	DC 24V (SPoE), DC 48V (PoE)
<b>Working Temperature</b>	-40°C to 50°C
<b>Storage Temperature</b>	-40°C to 60°C
<b>Working Humidity</b>	10%–90% RH
<b>IP Level</b>	IP30
<b>Interfaces</b>	Power In port, RJ45 Port, Alarm In Port, Doorbell Port
<b>Installation</b>	Flush mounting / Surface mounting
<b>Dimensions</b>	230 × 130 mm
<b>Additional Functions</b>	Elevator calling, guard station calling, IP camera integration, message/photo storage